

ŠKODA Rapid

Petrol engines

Technical specifications		1.2 MPI/55 kW	1.2 TSI/63 kW	1.2 TSI/77 kW	1.6 MPI/77 kW	1.6 MPI/77 kW (A)	1.4 TSI/90 kW (A)
Engine							
Engine type		petrol engine, in-line, liquid cooling system, DOHC, transverse in front	turbocharged petrol engine, in-line, liquid cooling system, direct injection, OHC, transverse in front		petrol engine, in-line, liquid cooling system, DOHC, transverse in front		turbocharged petrol engine, in-line, liquid cooling system, direct injection, DOHC, transverse in front
Cylinders		Э	4	4	4	4	4
Displacement	[cm ³]	1198	1197	1197	1598	1598	1390
Bore × Stroke	[mm × mm]	76.5 × 86.9	71.0 × 75.6	71.0 × 75.6	76.5 × 86.9	76.5 × 86.9	76.5 × 75.6
Max. engine performance/revs	[kW at rpm]	55/5400	63/4800	77/5000	77/5600	77/5600	90/5000
Max. torque/revs	[Nm at rpm]	112/3750	160/1500-3500	175/1550-4100	153/3800	153/3800	200/1500-4000
Compression ratio		10.5 : 1	10.0 : 1	10.0 : 1	10.5 : 1	10.5 : 1	10.0 : 1
Emission limit			EU 5	-	EU 4 (EU 2)	EU 4	EU 5
Fuel injection system		electronic multipoint fuel injection MPI	electronically controlled direct injection electronic multipoint		nt fuel injection MPI	electronically controlled direct injection	
Ignition		control unit controlled electronic ignition system					
Lubrication		force-feed lubrication with through-flow oil filter					
Fuel quality		unleaded petrol min. RON 95 (91)*					unleaded petrol min. RON 95
Transmission							
Wheel drive				front wh	ieel drive		
Clutch		hydraulic	raulic single dry clutch disc with membrane spring, asbestos free hydrodynamic converter				two coaxial dry multiple-disk clutch, electro-hydraulically operated
Transmission		manual 5-speed f	5-speed fully synchronized manual 6-speed fully synchronized		manual 5-speed fully synchronized	automatic 6-speed, with Tiptronic manual gear changing	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio		-3.77 -2.10 -1.28 V-0.88 V-0.67 R-3.18	I-3.77 II-1.95 III-1.28 IV-0.93 V-0.74 R-3.18	I-3.62 II-1.95 III-1.28 IV-0.93 V-0.74 VI-0.61 R-3.18	I-3.45 II-1.95 III-1.28 IV-0.88 V-0.67 R-3.18	I-4.15 II-2.37 III-1.56 IV-1.16 V-0.86 VI-0.69 R-3.39	I-3.50 II-2.09 III-1.34 IV-0.93 V-0.97 VI-0.78 VII-0.65 R-3.72
Axle ratio		4.929	3.625	3.933	4.571	4.067×0.906	4.800/3.429 R-4.500



ŠKODA Rapid

Petrol engines

Technical specifications	1.2 MPI/55 kW	1.2 TSI/63 kW	1.2 TSI/77 kW	1.6 MPI/77 kW	1.6 MPI/77 kW (A)	1.4 TSI/90 kW (A)	
Chassis							
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser						
Rear axle	compound link crank-axle						
Springs			nock absorbers with coil :				
Braking system	hydraulic dual-diagonal circuit braking system vacuum assisted with Dual Rate system						
Brake – front		disc brakes with inner cooling, with single/piston floating caliper					
Brake – rear			drum brakes			disc brakes	
Parking brake				rear wheels			
Steering system		direct rac	ck and pinion steering wi	th electrohydraulic powe	er steering		
Wheels	5]>	5J×14"		6J	×15"		
Tyres	175/7	'0 R14		185/	60 R15		
Body							
Body			5 door, two com	partment, 5 seater			
Drag coefficient c _w	0.303	0.300	0.308	0.	.301	0.297	
Outside dimensions							
Length [mm]			483			
Width [mm]			'06			
Height (at kerb weight) [mm]			161			
Wheel base [mm]	2602					
Clearance (at kerb weight) [mm			1	36			
Track front [mm	-	63			457		
E	[mm] 1500]4	494		
Inside dimensions							
Width of front seats [mm	1418						
Width of rear seats [mm	1428						
Headroom in front seats [mm							
Headroom in rear seats [mm							
Storage capacity [550						
Storage capacity with rear seatback folded	1490						
down	1		1-	.50			



ŠKODA Rapid

Petrol engines

Technical specifications		1.2 MPI/55 kW	1.2 TSI/63 kW	1.2 TSI/77 kW	1.6 MPI/77 kW	1.6 MPI/77 kW (A)	1.4 TSI/90 kW (A)
Weights				•			
Kerb weight – incl. driver**	[kg]	1135	1155	1175	1155	1195	1230
Payload – incl. driver**	[kg]			5	35		
Total weight	[kg]	1595	1615	1635	1615	1655	1690
Max. roof load	[kg]			- 7	5	-	
Max. trailer load w/o brakes	[kg]	560	570	580	570	590	610
Max. trailer load with brakes – 12%	[kg]	750	900	1100	1000	1000	1200
Max. trailer load with brakes – 8%	[kg]						
Max. nose weight	[kg]	50					
Liquids							
Tank capacity	[]	55					
Performance/consumption							
Maximum speed	[km/h]	175	183	195	193	192	206
Acceleration 0–100 km/h	[s]	13.9	11.8	10.3	10.6	11.9	9.5
Fuel consumption (1999/100/EC)		EU 5					
Consumption – urban	[l/100 km]	8.1	6.5 [5.9]	6.9 [6.3]	8.9	10.2	7.4 [6.8]
Consumption – extra-urban	[l/100 km]	4.6	4.4 [4.3]	4.6 [4.2]	4.9	6.0	4.8 [4.6]
Consumption – combined	[l/100 km]	5.9	5.1 [4.9]	5.4 [5.0]	6.4	7.5	5.8 [5.4]
CO ₂ emissions	[g/km]	137	119 [114]	125 [116]	152	180	134 [125]
Turning circle diameter	[m]] 10.2					

* Using low-octane fuel may affect engine performance. ** Figures apply to basic version, weight of driver 75 kg. [] Applies to Green tec.



ŠKODA Rapid

Diesel engines

Technical specifications	1.6 TDI CR DPF/66 kW	1.6 TDI CR DPF/66 kW (A)	1.6 TDI CR DPF/77 kW			
Engine		•				
Engine type	turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, high-pressure direct injection system, DOHC, transverse in front					
Cylinders	4 4		4			
Displacement [cm³]	1598	1598	1598			
Bore × Stroke [mm × mm]	79.5 × 80.5 79.5 × 80.5		79.5 × 80.5			
Max. engine performance/revs [kW at rpm]	66/4200	66/4200	77/4400			
Max. torque/revs [Nm at rpm]	230/1500-2500	230/1500-2500	250/1500-2500			
Compression ratio	16.5 : 1	16.5 : 1	16.5 : 1			
Emission limit	EL	5	EU 5 (EU 4)			
Fuel injection system	electronically	controlled high-pressure direct injection – comm	on-rail system			
Lubrication		force-feed lubrication with through-flow oil filter				
Fuel quality		diesel				
Transmission						
Wheel drive	front wheel drive					
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	two coaxial dry multiple-disk clutch, electro- hydraulically operated	hydraulic single dry clutch disc with membrane spring, asbestos free			
Transmission	manual 5-speed fully synchronized	automatic 7-speed, DSG, with Tiptronic manual gear changing	manual 5-speed fully synchronized			
Transmission ratio	I-3.78 II-2.12 III-1.27 IV-0.86 V-0.66 Z-3.60	I-3.50 II-2.09 III-1.34 IV-0.93 V-0.97 VI-0.78 VII-0.65 Z-3.72	EU 5: I-3.78 II-2.12 III-1.27 IV-0.86 V-0.66 Z-3.60 (EU 4: I-3.78 II-2.12 III-1.36 IV-0.97 V-0.73 Z-3.60)			
Axle ratio	3.158	4.438/3.227 Z-4.176	EU 5: 3.158 (EU 4: 3.647)			
Chassis		•	• •			
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser					
Rear axle	compound link crank-axle					
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs					
Braking system	hydraulic dual-diagonal circuit braking system vacuum assisted with Dual Rate system					
Brake – front	disc brakes with inner cooling, with single/piston floating caliper					
Brake – rear	drum brakes					
Parking brake	manual, on rear wheels					
Steering system	direct rack and pinion steering with electrohydraulic power steering					
Wheels	6J×15"					
Tyres	185/60 R15					



ŠKODA Rapid

Technical specifications		1.6 TDI CR DPF/66 kW	1.6 TDI CR DPF/66 kW (A)	1.6 TDI CR DPF/77 kW		
Body Body						
Body		5 door, two compartment, 5 seater				
Drag coefficient c _w		0.2	299	0.298		
Outside dimensions						
Length	[mm]		4483			
Width	[mm]		1706			
Height (at kerb weight)	[mm]		1461			
Wheel base	[mm]		2602			
Clearance (at kerb weight)	[mm]		136			
Track front	[mm]		1457			
Track rear	[mm]		1494			
Inside dimensions						
Width of front seats	[mm]		1418			
Width of rear seats	[mm]		1428			
Headroom in front seats	[mm]	1014				
Headroom in rear seats	[mm]		972			
Storage capacity	[]		550			
Storage capacity with rear seatback folded down	[1]	1490				
Weights						
Kerb weight – incl. driver**	[kg]	1265	1285	1265		
Payload – incl. driver**	[kg]		535			
Total weight	[kg]	1725	1745	1725		
Max. roof load	[kg]		75			
Max. trailer load w/o brakes	[kg]	630	640	630		
Max. trailer load with brakes – 12%	[kg]		1200			
Max. trailer load with brakes – 8%	[kg]		1200			
Max. nose weight	[kg]		50			
Liquids						
Tank capacity	[]		55			

Diesel engines



ŠKODA Rapid

Diesel engines

Technical specifications		1.6 TDI CR DPF/66 kW	1.6 TDI CR DPF/66 kW (A)	1.6 TDI CR DPF/77 kW	
Performance/consumption					
Maximum speed	[km/h]	184	184	190	
Acceleration 0–100 km/h	[s]	12.0	12.4	10.4	
Fuel consumption (1999/100/EC)			EU 5		
Consumption – urban	[l/100 km]	5.6 [4.8]	5.6	5.6 [4.8]	
Consumption – extra-urban	[l/100 km]	3.7 [3.4]	3.9	3.7 [3.4]	
Consumption – combined	[l/100 km]	4.4 [3.9]	4.5	4.4 [3.9]	
CO ₂ emissions	[g/km]	114 [104]	118	114 [104]	
Turning circle diameter	[m]		10.2		

** Figures apply to basic version, weight of driver 75 kg. [] Applies to Green tec.