



## ŠKODA Citigo

## Petrol engines

Technical specifications	1.0 MPI/44 kW	1.0 MPI/44 kW (A)	1.0 CNG/50 kW	1.0 MPI/55 kW	1.0 MPI/55 kW (A)
<b>Engine</b>					
Engine type	petrol engine, in-line, liquid cooling system, DOHC, transverse in front				
Cylinders	3				
Displacement [cm <sup>3</sup> ]	999				
Bore × Stroke [mm × mm]	74.5 × 76.4				
Max. engine performance/revs [kW at rpm]	44/5000-6000		50/6200		55/6200
Max. torque/revs [Nm at rpm]	95/3000-4300		90/3000		95/3000-4300
Compression ratio	10.5 : 1		11.5 : 1		10.5 : 1
Emission limit	EU 5				
Fuel injection system	electronic multipoint fuel injection MPI				
Ignition	control unit controlled electronic ignition system				
Lubrication	force-feed lubrication with through-flow oil filter				
Fuel quality	unleaded petrol min. RON 95 (91)*		unleaded petrol min. RON 95; natural gas - CNG	unleaded petrol min. RON 95 (91)*	
<b>Transmission</b>					
Wheel drive	front wheel drive				
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	controlled by electromechanical elements, single dry clutch disc with membrane spring, asbestos free	hydraulic single dry clutch disc with membrane spring, asbestos free	controlled by electromechanical elements, single dry clutch disc with membrane spring, asbestos free	
Transmission	manual 5-speed fully synchronized	automatic 5-speed, ASG, with manual gear changing	manual 5-speed fully synchronized		automatic 5-speed, ASG, with manual gear changing
Transmission ratio	I-3.64 II-1.95 III-1.27 IV-0.96 V-0.80 R-3.42				
Axle ratio	3.895			4.167	



## ŠKODA Citigo

## Petrol engines

Technical specifications	1.0 MPI/44 kW	1.0 MPI/44 kW (A)	1.0 CNG/50 kW	1.0 MPI/55 kW	1.0 MPI/55 kW (A)
<b>Chassis</b>					
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser				
Rear axle	compound link crank-axle				
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs				
Braking system	hydraulic dual-diagonal circuit braking system vacuum assisted with Dual Rate system				
Brake - front	disc brakes with inner cooling, with single/piston floating caliper				
Brake - rear	drum brakes				
Parking brake	manual, on rear wheels				
Steering system	direct rack and pinion steering with electrohydraulic power steering				
Steering wheel: diameter [mm]	375				
Wheels	5J×14"				
Tyres	165/70 R14 [175/65 R14]		175/65 R14	165/70 R14 [175/65 R14]	
<b>Body</b>					
Body	3-door {5-door}, two compartment, 4 seater				
Drag coefficient $c_w$	0.33		0.34	0.33	
<b>Outside dimensions</b>					
Length [mm]	3563				
Width [mm]	1641 {1645}				
Height (at kerb weight) [mm]	1478 [1463]		1480	1478 [1463]	
Wheel base [mm]	2420		2421	2420	
Clearance (at kerb weight) [mm]	136 [121]				
Height of the loading sill (at kerb weight) [mm]	769 [753]		773	769 [753]	
Track front [mm]	1428				
Track rear [mm]	1424				
<b>Inside dimensions</b>					
Width of front seats [mm]	1417 {1369}				
Width of rear seats [mm]	1389 {1388}				
Headroom in front seats [mm]	993				
Headroom in rear seats [mm]	947				
Storage capacity [l]	251				
Storage capacity - with rear seatback folded down [l]	951 {959}		913 {921}	951 {959}	



## ŠKODA Citigo

## Petrol engines

Technical specifications		1.0 MPI/44 kW	1.0 MPI/44 kW (A)	1.0 CNG/50 kW	1.0 MPI/55 kW	1.0 MPI/55 kW (A)
<b>Weights</b>						
Kerb weight - incl. driver**	[kg]	929 [940]	932	1031	929 [940]	932
Payload - incl. driver**	[kg]	436 [425]	433	414	436 [425]	433
Total weight	[kg]	1290		1370	1290	
<b>Liquids</b>						
Tank capacity	[l]	35		petrol: 10; CNG: 72 (12 kg)	35	
<b>Performance/consumption</b>						
Maximum speed	[km/h]	160 [161]	160	164	171 [172]	171
Acceleration 0-100 km/h	[s]	14.4	15.3	16.3	13.2	13.9
Fuel consumption (1999/100/EC)		EU 5				
Consumption - urban	[l/100 km]	5.6 [5.0]	5.3	5.5 m <sup>3</sup> /100 km	5.9 [5.1]	5.5
Consumption - extra-urban	[l/100 km]	3.9 [3.6]	3.9	3.8 m <sup>3</sup> /100 km	4.0 [3.7]	4.0
Consumption - combined	[l/100 km]	4.5 [4.1]	4.4	4.4 m <sup>3</sup> /100 km	4.7 [4.2]	4.5
CO <sub>2</sub> emissions	[g/km]	105 [95]	103	79	108 [98]	105
Turning circle diameter	[m]	9.8				

\* Using low-octane fuel may affect engine performance.

\*\* Figures apply to basic version, weight of driver 75 kg.

[ ] Applies to Green tec.

{ } Applies to 5-door version.