

Zarooq unveils details about its SandRacer in press conference during Abu Dhabi GP week

Sand racing car, made in UAE



First Press conference held in the Sofitel the Palm, Dubai gathering the whole team during Abu Dhabi Grand Prix week

Zarooq Motors had invited the press in the Sofitel the Palm Dubai, a few days before the Abu Dhabi Grand Prix. "The timing and the location allowed us to have everyone around the table, including Campos Racing team (Adrian Campos, CEO and Rio Haryanto, GP2 driver)" noted Bruno Laffite, Operations Director.

"It was a unique moment for us to exchange with the press and answer all their questions" commented Mohammed Al Qadi, Motorsport director "and we were glad to have attracted such a crowd of journalists, highlighting the level of interest we have generated locally in the UAE, in the Gulf but also internationally."

The genesis of Zarooq Motors is embedded in UAE motorsport ...

ZarooqMotors.com

"The Zarooq SandRacer was created in order to be able to organize an Off-road single-make championship and operate a sand racing track in Dubai" explains Mohammed al Qadi. "We have all the necessary skills in the UAE, from the design to the actual manufacturing of the chassis and the body as well as the final assembly, with our partners JJSpecial" added Mohammed. "We wanted the car to be road legal, with AC, because we want it to be as practical as possible, even if it is a racing car" said Bruno Laffite. "The support and insights from the industry we get thanks to our partnership with Motorsport professionals like Campos Racing is of great value today for the car and tomorrow for our championship", he added.

...with an objective of being a sustainable UAE car manufacturer and motorsport provider

Zarooq Motors aims at building a sustainable brand synonymous with off-road capability, racing-grade performance and iconic look. "We don't aim at being a large scale manufacturer, but a solid niche player consistently delivering innovative and reliable cars" underlines Mohammed. "We are an Emirati company and we want to show the world what we are capable of."

contact@ZarooqMotors.com

ZarooqMotors on Social Networks:

<u>زاروق# #zarooq #sandracer</u>







The aggressive and iconic look of the car revealed

Anthony Jannarelly, came to global automotive industry fame as the designer of the W Motors Lykan and Fenyr. As part of JJSpecial, the Zarooq SandRacer is his latest creation.

"It had to be fit for purpose, of course, hence the significant ground clearance, limited overhang or the room necessary for significant suspension travel. It also had to meet the standards to be road legal, yet we clearly focused on designing a car that is unique, aggressive and we hope, one day, iconic" Anthony Jannarelly said.



The details of the car's performance were covered with the GP engineers from Campos Racing who designed it

The details of the car performance and engineering designs were discussed at length with Philippe Gautheron and Emilio Lozano, from Campos Racing, as well as Frederic Juillot from JJSpecial in charge of the manufacturing workshop. "We chose all our parts and partners in order to offer the best racing performance, from engine supplier, tires but also suspensions which are critical for Off-road Performance" remarked Bruno Laffite.



The development strategy is ambitious but realistic

Zarooq Motors management has devised a realistic development plan, primarily focused on developing sales in the UAE and the gulf, aiming at drivers who want a high performance sand racing car, which is affordable and easy to maintain; the car can also cater of course to all the car enthusiasts of the region. "We actually have some people interested in importing the car in the gulf but also in Europe" mentioned Mohammed Al Qadi. "We will concentrate on exports and launching new products once our local sales are sustainable"

In parallel, and in order to foster the development of the local championship, Zarooq Motors is initiating a "Dubai Off-Road Racing Track" to host races but also corporate events in a premium and safe environment dedicated to sand racing. "You will be able to see Dubai " c_{r} z_{s} " in Arabic: as part of the track design" explains Mohammed Al Qadi.

Car to be shown to journalists and to the public in January 2016

Mohammed explained: "Chassis is now finished, the engine and wiring are in place and working, the body molds are being sculpted, and we are just waiting for a few parts to arrive to finalize the assembly, in December". "If all goes well, we should be able to show the car to the journalists and then to the public very soon. Expect to be able to see it here in the Sofitel the Palm in a few weeks..." said Iannis Mardell.

"Of course, we are conducting a series of tests to proof the car and then we will take the road homologation"

As a result, the journalists and first clients should be able to test the car in early 2016.





Technical specs (subject to changes)

CHASS CHASS Length (min) 0.200 Naticape head (min) 0.200 Naticape head (min) 0.200 Charlow (General) 0.200 Grand (General) 0.200 Charlow (General) 0.200 Math speed (Min) 0.200 Math speed				
Status 504 Bolicase heigh (mm) 2160 - 2100 Cartor 700 Apprach Augle (degrees) 515 Bolicase heigh (degrees) 315 Bolicase heigh (degrees) 315 Barro Deefnag (mn) 515 Bolicase heigh (degrees) 315 Barro Deefnag (mn) 515 Bolicase heigh (degrees) Mindet 355 state hube Mannam bulbeds: 700 Parto Perform 200 kph - 190 Mannam bulbeds: 700 kph - 190 Bolicase heigh 700 kph - 190 Bolicase heigh 304 Control 700 kph - 190 Bolicase heigh 304 Control 348 Bolicase heigh 304 Control 600 kph - 190 Bolicase heigh 304 Control 600 kph - 190 Bolicase heigh 600 kph - 190 Bolicase height 200 kph - 190 Bolicase height	CHASSIS			
Irack (mm) 122 Irack (mm) 223 Irack (mm) 223 Irack (mm) 223 Irack (mm) 704 Irack (mm) 704 Irack (mm) 704 Irack (mm) 704 Irack (mm) 233 Irack (mm) 235 Irack (mm) 235 Irack (mm) 235 Irack (mm) 60% kar. 40% front 200 Urb Add (datababae) 60% kar. 40% front 10000 Urb Add (databae) 60% kar. 40% front	Length (mm)	4200	(3)	
1 210 - 2100 Nivelasse (nm) Rer Overlang (nm) Statuse (nm) Nordige (degrees) Namium bulkeads. Displacement (cr) Statuse (nm) Contage (nm)	Width (mm)	2084		
First krml 2160 - 2100 Witeklass (mm) 700 Rer Orefrig (mm) 700 Approach Aug (edgress) 535 Bang Oref Age (edgress) 535 Ham (bor Age (edgress)) 535 Ham (bor Age (edgress)) 535 Amm orefrig (edgress) 535 Mass speed (kn/h) 200 kph - 150 Struter 500 kr (ear - 40% front Brag (erg (mm)) 500 kr (ear - 40% front Digplacement (cf) 504 Digplacement (cf) 545 Cylinders 54 Cylinders 54 <	Rollcage height (mm)	1220	Zaroo Clee Daroo	
Forto overhang (mm) 00 Rev Overhang (mm) 03 Grand classer (mm) 33 Departure angle (degrees) 33 Rum Overhang (degrees) 33 Struture medication and ministration PEROFMANCE Normality (degrees) Numise (degrees) 00 Mass speed (mr/h) 00 Rev (her (her) 00 Struture 00 Mass speed (mr/h) 00 Rev (her) 00 Struture 00 Rev (her) 00 Struture 00 Mass speed (mr/h) 00 Struture 00 Rev (her) 00 Struture 00 Rev (her) 00 Struture (her) 00 Rev (her)	Track (mm)			
Forto overhang (mm) 00 Rev Overhang (mm) 03 Grand classer (mm) 33 Departure angle (degrees) 33 Rum Overhang (degrees) 33 Struture medication and ministration PEROFMANCE Normality (degrees) Numise (degrees) 00 Mass speed (mr/h) 00 Rev (her (her) 00 Struture 00 Mass speed (mr/h) 00 Rev (her) 00 Struture 00 Rev (her) 00 Struture 00 Mass speed (mr/h) 00 Struture 00 Rev (her) 00 Struture 00 Rev (her) 00 Struture (her) 00 Rev (her)	Wheelbase (mm)	2820		
Rev Overhang form 704 Approch Ange (edgrees) 325 Bargo Over Ange (edgrees) 230 Structure Weded 5355 steel tube Prosphate Ange (edgrees) 200 1050 Weded 5355 steel tube 000 1050 Mess weed (en/h) 200 km - 100 Numium bubberas 200 km - 100 Prosphate Ange (edgrees) 200 km - 100 Numium bubberas 200 km - 100 Numium bubberas 600 km - 100 Poplacement (c) 304 Barte (enm) 324 Coludars 6600 rpm Engine position Central - rear Suppose ment (c) 324 Barte (enm) 324 Coludars 6600 rpm Engine position Central - rear Suppose ment (c) 324 Barter (enm) 324 Coludars 6600 rpm Engine position Central - rear Suppose 32/ 34 m Barter (enm) 32/ 34 m Columars 32/ 34 m Barter (enm) 32/ 34 m Columars		700		
Application Angle (degrees) 45% Grand (darge (degrees)) 33% Name Over Angle (degrees) 33% Name Speed (rsh) 300 Name Speed (rsh) 300 Name Speed (rsh) 300 Stock (rmn) 34% Stock (rmn) 31% Stock (rmn) 32% Stock (rmn) 32% Stock (rmn) 32% Stock (rmn) 34%<				
Grand Clearance (mn) 315 Departure angle (degrees) 259 Structure Departure angle (degrees) Welded 5355 steel tube Departure angle Doparture angle (degrees) 259 Structure Departure angle Mer Weight distribution 60% Rear-40% Front Turning Circle (n) 200 kph - TBC Doparement (c.) 364 Struck (mn) 81.4 Conders 6 Doparement (c.) 304 Targue (Nm) 371 Brance (mn) 372 Conders 6 Power (hp) 374 Targue (Nm) 371 Brance (mn) 2614 Deparement (c.) 374 Deparement (c.) 374 Brance (mn) 274 Brance (mn) 274 Deparement (c.) 374 Brance (mn) 280 Engine position Central - rear Struck (mn) 281 Coli Spring K TBO Brance (mn) 317 36 m Deparement (c.) <td< td=""><td></td><td></td><td></td><td>THE AT DEF ROAD</td></td<>				THE AT DEF ROAD
Same Dever rangle (digenes) Rame Dever rangle (digenes) Same Dever rangle (digenes) Rame Dever rangle (digenes) Same Dever rangle (digenes) Struttre Departure angle (digenes) PERFORMANT Composition 1000-1050 Weight dig (wind) 100 Max speed (wind) 100 Charles 1000-1050 Max speed (wind) 100 Charles 100 Performant Conte (m) 100 Displacement (c) 3.88 Stack (mn) 101 Charles 6.000 pm Rever (bit) 3.01 Charles 6.000 pm Rever (bit) 2.000 Stack (mn) Carles - 4.000 Rever (bit) 3.01 Stack (mn) Carles - 4.000 Rever (bit) 3.01 Stack (mn) Carles - 4.000 Rever (bit) 2.000 Stack (mn) Carles - 4.000 Rever (bit) 2.000 Stack (mn) 2.000 Rever (bit) 3.012 Stack (mn) 3.212 Rever (mn) 3.312 </td <td></td> <td></td> <td>E</td> <td></td>			E	
Ramp Over Angle (signess) 29 Ramp Over Angle (signess) Robert and state (singest) Struture Auminium buildheads. Weight distribution 60% Rear - 40% Front Namis Speel (sing) 200 Hps - 16C Name Speel (sing) 201 Hps - 16C Note (mn) 61 Spee (mn) 61 Spee (mn) 61 Spee (mn) 61 Torque (Nn) 61 Torque (mn) 61 Spee (mn) 61 Spee (mn) 61 Torque (mn) 61 Torque (mn) 61 Spee (m				Zaroz Ziteš Quanta Chen Chen Chen Chen Chen Chen Chen Chen
Weider 3353 street lube Preprogrammed over castel finish Aurinium buildheads. Preprogrammed over castel finish Aurinium buildheads. Weider distribution Weider distribution				
Prosperated, provider costed finited Munitum bulkheads. Structure Image: Coste (Init) Mass speed (Init) 100-1550 Weight distribution 100-1550 Mass speed (Init) 100-150 Mass speed (Init) 1	Namp Over Angle (degrees)			
Acturitie Auminieum buikheeds. PERFORMANCE Kerk Weight (bg) 100-1950 Mass geed (m/h) 200 kph. TBC Fuel capacity (i) 100 Biglacement (cc) 3498 Bore (mm) 81.4 Cylinders 6 Power (bh) 30.4 Torque (hm) 37.1 Inginge position Central - rear Stroke (mn) 600 rpm Tage position Central - rear Stroke (mn) 37.1 Inginge position Central - rear Stroke (mn) 600 rpm Tage position Central - rear Stroke (mn) 37.1 Inginge position Central - rear Stroke (mn) 37.1 Tage (bm) 37.1 Braine (bm) Central - rear Stroke (mn) Stroke (mn) Stroke (mn) Stroke (mn) <				The manner and the second se
Field Read Read (Kig) 1000-1053 Weight distilution 60% Rear - 40% Front Timing Circle (m) 12 Max speed (Kin/h) 20(b) h- 12C Evelope (Kin/h) 3.498 Bore (mm) 95.5 Stroke (mm) 91.5 Stroke (mm) 91.6 Torque (kin/h) 3.498 Bore (mm) 91.5 Stroke (mm) 91.6 Torque (kin/h) 3.498 Bore (mm) 92.5 Stroke (mm) 93.4 Torque (kin/h) 3.10 Injection Indirect multi-por grouped fuel injection Engine position Central - rear Stroke (mm) 2.40 Stroke (mm) 2.40 Stroke (mm) 2.41 Bore (mn) 2.41 Braine (Stroke (Stro	Chrustian		A summer of	Province of the
Key Weight (fig) 1000-1050 Weight distribution 60% Rear - 40% Front Turning Circle (m) 12 Mass speed (lm/h) 200 kph - TBC Fuel capacity (l) 110 Broin 95.5 Stroke (mn) 81.4 Cylinders 6 Power (bh) 30.4 Torque (Nm) 161.4 Cylinders 6 Power (bh) 30.4 Torque (Nm) 161.4 Engine position Certaral rear Forth 1640 capacity (l) Torque (Nm) 6600 rpm Engine position Certaral - rear Forth 1640 capacity (l) Stroke (mn) 240 Stroke (mn) 317 mm Targue position Certaral - rear Stroke (mn) 317 mm Torque (Mn) 317 mm Torque (Mn) 317 mm Stroke (mn) 317 mm Torque (Mn) 317 mm Torque (Mn) 317 mm Torque (Mn) 317 mm Torque (Mn) 317 mm		Aluminium bulkheads.	ALL PARTY	
Wreight distribution 60% Rear-40% Front Name speed (km/h) 200 kph - TBC Leid apacthy (I) 110 Excise 3.498 Bore (mn) 55.5 Stoke (mm) 66.0 Oppier (Mn) 30.4 Torque (Nn) 30.4 Engine (moni) 30.4 Torque (Nn) 30.4 Engine position Central - rear Forter Interposition Central - rear Forter Interposition 20.0 States (mm) 3.04 Torque (Mn) 3.04 Engine position Central - rear Fort Senting arm Spring KTBD Basel (mm) 2.00 States (mm) 2.01 Fort Senting arm Spring KTBD Basel (mm) 2.01 Fort Senting arm Spring KTBD Basel (mm) 2.02 States (mm) 2.02 States (mm) 3.31 / 34 / 40 Basel (mm) 3.31 / 34 / 40 Basel (mm) 3.31 / 34 / 40 Basel (mm) 3.31 / 34 / 40 Base				
Tange Cricle (m) 12 Max speed (km/h) 200 kph - TB Fuel capacity (l) 110 Dispacement (c) 3,498 Borg (mn) 95.5 Stroke (mn) 81.44 Orgue (bhg) 304 Torque (h) 101 Breide ment (c) 304 Dispacement (c) 304 Torque (h) 311 Injection Indirect multi-port grouped fuel injection Rev (min) Central - rear Stroke (m) 240 Stroke (m) 312 Injection Indirect multi-port grouped fuel injection Rev (min) Central - rear Stroke (m) 240 Dispacement (m) 321 Indirect multi-port grouped fuel injection Indirect multi-port grouped fuel injection Rev (m) 104 Barpers 240 Porter 3342.25 R15 Barpers 240 Porter (m) 337.48 cm Barpers 240 See (adjustable forter trains (m) Stroke (m) 327.81 cm				
Max speed (km/h) 200 kph - TBC Leide capacity (i) 10 ENGIN 3.498 Bore (mm) 3.55 Stroke (mm) 81.4 Cylinders 6 Power (bhp) 304 Torque (Nm) 311 Illection Indirect multi-port grouped fuel injection Rev imit 6600 rpm Egine position Central - rear Final Bankinki Barker (mn) 240 Spring K TBD Spring K TBD Final Rev (mn) 240 Spring K TBD Spring K TBD Final Rev (mn) 240 Spring K TBD Spring K TBD Final Rev (mn) 240 Spring K TBD Spring K TBD Brakes (mn) 240 With 317 nm Spring K TBD Spring K TBD Final Review 317 nm Spring K TBD Spring K TBD Final Review 317 nm Spring K TBD Spring K TBD Spring K TBD Spring K TBD Spring K TBD Spring K	-			
Pare Lagacity (I) 110 Displacement (cc) 3,498 Bore (mn) 95.5 Stroke (mn) 95.6 Stroke (mn) 6 Olyndacement (cc) 6 Power (bhp) 304 Torque (Nm) 371 Injection Indirect multi-port grouped fuel injection Rev (imit) Genome (Nm) Engine position Certral - rear Stroke (mn) Certral - rear Stroke (mn) Stroke (mn) Mark (ms) Stroke (mn) Rev (ms) Certral - rear Stroke (mn)				
Field capacity (i) 110 ENGINE Displacement (cc) 3.488 Bore (mm) 95.5 Stroke (mm) 61 Cylinders 6 Power (bhp) 304 Torque (Nm) 371 Indirect multi-port grouped fuel injection 6600 rpm Rey limit 6600 rpm Engine position Central - ear Support (Stroke (Stro	Max speed (km/h)			JEJ Special Commences
Displacement (cc) 3.498 Bore (mm) 95.5 Stroke (mm) 31.4 Cylinders 6 Power (bhp) 331 Injection Indirect multi-port grouped fuel injection Rev limit 6600 rpm Egine position Central - rear Stroke (mm) Stroke (mm)		110		
Bore (mm) 95.5 Stroke (mm) 81.4 Cylinders 6 Power (hp) 304 Torque (hm) 13.1 Injection Indirect multi-port grouped fuel injection Rev limit 6600 rpm Engine position Central - rear Wint 6600 rpm Engine position Central - rear Wint 6000 rpm Rev limit 6000 rpm Engine position Central - rear Wint 6000 rpm Rear Trailing arm Brakes (mm) Ventilated Specis Adjustable front rear bias Type 33/2 A4 cm Rim 15'/ 38 cm Winth 31/7 rm Diameter 33'/ 44 cm Rim 15'/ 38 cm Winth 31/7 rm Diameter 12' Approved four point quick releases Seet bet 2' E Approved four point quick releases Set bet 2' E Approved four point quick releases Rack and pinon cast alloy steering rack 1.7 turns lock to lock Colapsible dispilay, speedometer, tachometer, w	ENGINE			
Stroke (mm) 81.4 Cylinders 6 Power (bhp) 30.4 Torque (Mm) 37.1 Ingiction Indirect multi-port grouped fuel injection Rev limit 6600 rpm Engine position Central - rear Stroke (mm) Central - rear Stroke (mm) Stroke (mm) Coline Stroke (mm) Engine position Central - rear Stroke (mm) Central - rear Front Independent triangle Rear Training arm Brackitos Adjustable for rear bias Type 33:12.5 R15 Diameter 33'/ 48 cm Rim 31'/ 5'/ 38 cm Vidth 317 mm O'Here Dony structural fibergiass moulded. Composite mix Seats Individual sect units composite overn (oth, adjustable. Seat belt 2' E Approved four point quick release fuel mannesses Seat belt 2' E Approved four point quick release fuel mannesses Seat and printin cast alloy steering rack 1.7 turns lock to lock Collagaide offset steering column. Adjustable. Steering 305m race sus	Displacement (cc)	3,498		
Cylinders 6 Daver (bip) 304 Dower (bip) 304 Drive 2VD Torque (m) 371 Dampers SUSPENSION Rev limit 6600 rpm Engine position Central - rear SWIME Contral - rear Fox 980-02-000 // fox 983-02-075 Coll Dampers Spring KTBD Engine position Central - rear For 1 Rear Tarling arm BRAKING Brakes (nm) 240 Brakes (nm) 240 Ventilated Speces Adjustable front trear bias Training arm Brakes (nm) 240 Speces Adjustable front trear bias Type 3312,5 R15 Dameter Bird (Stream) Writh 337 // 84 cm Writh 337 rm Orter Body Seats Individual seat units composite woven cloth, adjustable. Seat belt 2* E Approved four point quick release full harnesses Seats Seat belt 2* E Approved four point quick release full harnesses Rear of gainon cast alloy steering avk.1.2 truns lok to lock Collapsible offset steering volume. Justable ro	Bore (mm)	95.5	GEARBOX AND TRANSMISSION	N
Power (bhp) 304 Torque (Mm) 371 Injection Indirect multi-port grouped fuel injection Rev limit 6600 rpm Engine position Central - rear Fort Independent triangle Rear Trailing arm BRAKING Brakes (mm) Species Adjustable front rear bias View 33/12.5 R15 Diameter 33'/ 84 cm Rim 13'/ 84 cm Width 312 mm Offlee Offlee Body Non structural fiberglass moulded. Composite mix Seats Individual seat units composite mix Steering 325 mm Steering 325 mm Brake and pinion cast alloy steering rack 1.1 turns lock to lock Collapsible offset steering column. Adjustable col ends Steering lamp, reverse tangen, unumber plate lam	Stroke (mm)	81.4	Transmission	6 speed automatic
Power (hph) 304 Drive 2WD Torque (hm) 371 Supersion Darpers Fox 980-02-009 // Fox 983-02-075 Rev linit 6600 rpm For 1 Dirpers For 980-02-009 // Fox 983-02-075 Engine position Central - rear For 1 Dirpers For 1 Dirpers For 1 Central - rear For 1 Brakes (mm) 240 Species Adjustable for mare bias Trailing arm Brakes (mm) 240 Dirpers Dirpers Vertilated Species Adjustable for mare bias Dirpers View 3312.5 R15 Diameter Biarkes (mm) 240 Diameter 337.4 Adv m Rim 15' / 38 cm View View 0 Or View Diameter Biarkes Diameter Biarkes Diameter Sects Diameter Biarkes Diameter Sects Diadustable for dot ends Diatustable Diatu	Cylinders	6	Paddle shift	ves
Injection Indirect multi-port grouped fuel injection Dampers Fox 980-02-009 // fox 983-02-0075 Rev limit 6600 rpm Coil Spring K TBD Engine position Central - rear Front Indirecent multi-port grouped fuel injection Fort Spring K TBD Rear Trailing arm BRAKING Brakes (mm) 240 Spess Adjustable front rear blas Yre Diameter 337 / 94 cm Rim Rim 317 / 94 cm Rim Width 317 mm Orther Diameter 337 / 94 cm Rim Kinh 563 ses Prove Diameter 317 / 94 cm Rim Kinh 317 mm Orther Diameter 317 / 94 cm Rim Kinh 317 mm Orther Brody Non structural fiberglass moulded. Composite mix Seats Seats belt 2" E Approved for point quick release full harnesses Seate belt 2" E Approved for point quick release full harnesses Seate belt 2" E Approved for point quick release full harnesses Seate belt <	Power (bhp)	304	Drive	
Injection Indirect multi-port grouped fuel injection Dampers Fox 980-02-009 // fox 983-02-0075 Rev limit 6600 rpm Coil Spring K TBD Engine position Central - rear Front Indirecent multi-port grouped fuel injection Fort Spring K TBD Rear Trailing arm BRAKING Brakes (mm) 240 Spess Adjustable front rear blas Yre Diameter 337 / 94 cm Rim Rim 317 / 94 cm Rim Width 317 mm Orther Diameter 337 / 94 cm Rim Kinh 563 ses Prove Diameter 317 / 94 cm Rim Kinh 317 mm Orther Diameter 317 / 94 cm Rim Kinh 317 mm Orther Brody Non structural fiberglass moulded. Composite mix Seats Seats belt 2" E Approved for point quick release full harnesses Seate belt 2" E Approved for point quick release full harnesses Seate belt 2" E Approved for point quick release full harnesses Seate belt <	Torque (Nm)	371	SUSPENSION	
Rev limit 6600 rpm Coll Spring KTBD Engine position Central - rear Rear Independent triangle Rear Brakes (mm) 240 Ventilated Specs Adjustable front rear bias Tyre 33*/ 84 cm Diameter 33*/ 84 cm Nimit 15' / 38 cm With 317 nm OTHER Seats Body Non structural fiberglass moulded. Composite mix Seats Individual seat units composite woven cloth, adjustable. Seats 2'f Approved four point quick release full harnesses Seats 2'f Approved four point quick release full harnesses Steering 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip Warning lights: lgnition, lights, brake, oil, beam, indicators, alarm. Projector headlangs. LD indicators, stap/tal/side/repaters.		Indirect multi-port grouped fuel injection	Dampers	Fox 980 -02-009 // Fox 983-02-075
Engine position Central - rear Font Independent triangle Reak NUNG Brakes (mm) 240 Brakes (mm) 240 Ventilated Specs Adjustable front rear bias Type Type 33', 84 cm Brakes (mm) 10', 15', 73 dc Diameter 33', 84 cm Brakes (mm) 10', 15', 73 dc Non structural fiberglass moulded. Composite mix Brakes (mm) 317 mm OTHER Brakes (mm) 317 mm Brakes (mm) 317 mm 0', 15', 13', 20', 20', 20', 20', 20', 20', 20', 20	Rev limit		Coil	Spring K TBD
Rear I Trailing arm Rear I I I I I I I I I I I I I I I I I I I	Engine position	· · · · · · · · · · · · · · · · · · ·	Front	Independent triangle
Brakes (mm) 240 Vertilized Adjustable front trear bias Tyre 33x12.5 R15 Diameter 33", / 84 cm Rim 15", / 38 cm With 317 nm OTHER 0 Body Non structural fiberglass moulded. Composite mix Seats Individual seat units composite woven cloth, adjustable. Seats 2"E Approved four point quick release full harnesses Seats Individual seat units composite woven cloth, adjustable. Seats 2"E Approved four point quick release full harnesses Seate left 2"E Approved four point quick release full harnesses Steering 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: lightion, lights, brake, oil, beam, indicators, atory. Northruments Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: lightion, lights, brake, oil, beam, indicators, atory. Rear forg lamp, reverse lamp, number plate lamp. Horm. 3 way closed box	0 1 1 1 1 1		Rear	Trailing arm
Specs Specs Tyre 33''. / 84 cm Diameter 33''. / 84 cm Rim 15''. / 38 cm Width 317 mm OTHER Body Seats Individual seat units composite woven cloth, adjustable. 2'' E Approved four point quick release full harnesses Seats 2'' E Approved four point quick release full harnesses Steering 305mm race suede covered steering rolum. Adjustable of ends 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: ignition, lights, brake, oi, beam, indicators, alarm. Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: ignition, lights, brake, oi, beam, indicators, alarm. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed low			BRAKING	
Specs Adjustable front rear bias Tyre 33x12.5 R15 Diameter 33" / 44 cm Rim 15" / 38 cm Width 317 mm OTHER Individual seat units composite mix Seats belt 2" E Approved four point quick reases full harmesses Steering 305mm race suede covered steering wheel Steering 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warming lights: lightion, lights, brake, oil, beam, indicators, alarm. Projector headiams. LED indicators, stard, alwolded steering. Projector headiams. LED indicators, stard, alwolded steering.			Brakes (mm)	
Yre 33x12.5 R15 Diameter 33", / 84 cm Nimeter 15", / 38 cm Width 317 nm OTHER 317 nm Body Non structural fiberglass moulded. Composite mix Individual seat units composite woven cloth, adjustable. 32" E Approved four point quick release full harnesses Seat belt 2" E Approved four point quick release full harnesses Steering 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: lagnich lights/prake, oil, beam, indicators, alarm. Noriettruents LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: lagnich lights/peralers. Rear fog lamp, reverse lamp, number plate lamp. Hom. 3 way closed loc	9			
Diameter 33" / 84 cm Rim 15" / 38 cm Width 317 mm OTHER Body Seats Individual seat units composite mix Seats 2" E Approved four point quick release full harmesses Seats 2" E Approved four point quick release full harmesses Steering 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warming lights: lagind; Light onicitators, alarm, Projector headmaps. LED indicators, alarm, Rear fog lamp, reverse lamp, number plate lamp, Hom. 3 way closed box	زارق م			
Rim 15"/38 cm Width 317 mm OTHER Body Seats Individual seat units composite woven cloth, adjustable. Seat belt 2" E Approved four point quick release full harnesses Seats Rack and pinion cast alloy steering rack 1.7 turns lock to lock Collapsible offset steering column. Adjustable rod ends 305mm race suede covered steering wheel Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: lagnich, lights, brake, oil, beam, indicators, alarm. Rear fog lamp, reverse lamp, number plate lamp. Hom. 3 way closed loc				
Width 317 mm OTHER Body Non structural fiberglass moulded. Composite mix Body Individual seat units composite woven cloth, adjustable. Seat belt 2" E Approved four point quick release full harmesses Steering 305mm race suede covered steering routed. Steering 305mm race suede covered steering wheel Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: landicators, alarm. Rear fog lamp, reverse lamp, number plate lamp. Hom. 3 way closed loop				
OTHER Body Seats Steering Non structural fiberglass moulded. Composite mix Individual seat units composite woven cloth, adjustable. Steering 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: Ignition, lights, brake, oil, beam, indicators, alarn. Projector heads. Rear fog lamp, reverse lamp, number plate lamp. Hom. 3 way closed bot <td></td> <td></td> <td></td> <td></td>				
Body Non structural fiberglass moulded. Composite mix Seats Individual seat units composite woven cloth, adjustable. Seat belt 2" E Approved four point quick release full harnesses Steering 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Non structural fiberglass moulded. Composite mix Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loop	6400			317 mm
Body Non structural fiberglass moulded. Composite mix Seats Individual seat units composite woven cloth, adjustable. 2" E Approved four point quick release full harmesses Seat belt 2" E Approved four point quick release full harmesses Steering 305mm race suede covered steering wheel Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: lights, brake, oil, beam, indicators, alarm. Projector headamp.tel dimictor, 2 alarm. Rear fog lamp, reverse lamp, number plate lamp. Hom. 3 way closed loc	CHIEAT OFF	ROAD	OTHER	
Body Non structural intergrass moduled. Composite mixes Seats Individual seat units composite woven cloth, adjustable. Seat belt 2" E Approved four point quick release full harmesses Rack and pinion cast alloy steering rack 1.7 turns lock to lock Collapsible offset steering column. Adjustable rod ends 305mm race suede covered steering wheel Instruments Projector headmaps. LEDD Digital display, speedometer, tachometer, water, fuel, odo, trip.Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Projector headmaps. LEDD indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loc				
Seats Individual seat units composite woven cloth, adjustable. 2" E Approved four point quick release full harnesses Rack and pinion cast alloy steering rack 1.7 turns lock to lock Collapsible offset steering column. Adjustable rod ends 305mm race suede covered steering wheel LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Projector headlamps. LED indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loc			Body	Non structural fiberglass moulded. Composite mix
Seat belt 2" E Approved four point quick release full harnesses Rack and pinion cast alloy steering rack 1.7 turns lock to lock Collapsible offset steering column. Adjustable rod ends 305mm race suede covered steering wheel Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Projector headlamps. LED indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loc				
Steering Steering Notice Steering Notice Steering Notice Steering Steering Steering tiditable S				
Steering Collapsible offset steering column. Adjustable rod ends 305mm race suede covered steering wheel Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Projector headlamps. LED indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loc	10			
Steering 305mm race suede covered steering wheel Instruments LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Projector headlamps. LED indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loop				
LCD Digital display, speedometer, tachometer, water, fuel, odo, trip. Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Projector headlamps. LED indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Hom. 3 way closed loc				
Instruments trip. Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Projector headlamps. LED indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loc			Steering	305mm race suede covered steering wheel
Instruments trip. Warning lights: Ignition, lights, brake, oil, beam, indicators, alarm. Projector headlamps. LED indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loc				
Projector headlamps. LED indicators, stop/tail/side/repeaters. Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loc				LCD Digital display, speedometer, tachometer, water, fuel, odo,
Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loc			Instruments	
Road Equipment Front and rear mudguards.		July Januardy 10/2015 JSJ Special /		Rear fog lamp, reverse lamp, number plate lamp. Horn. 3 way closed loop.
			Road Equipment	Front and rear mudguards.

Options available (non exhaustive)

Performance	Finishing
• 400hp, 500hp engine preparation	Carbon fiber interior / exterior
• Dynamic Off-Road suspension	Infotainment system
High capacity reservoir	Comfort seats
Performance gearbox	• Spare wheel
• Off-Road wheels and tyres	• Car cover
Performance brakes	Bespoke body
• Performance exhaust system	LED lights
Special FIA pack	• Paint and stripe
	• Cupholder, glove box, etc.

 $\underline{contact@ZarooqMotors.com}$

ZarooqMotors on Social Networks:

<u>زاروق# #sandracer زاروق</u>



- **1**



campos



S O F I T E L THE PALM, DUBAI



Variations



End